

TCB

**GRANT OF EQUIPMENT
AUTHORIZATION**

TCB

Certification

**Issued Under the Authority of the
Federal Communications Commission**

By:

**CKC Certification Services, LLC
5046 Sierra Pines
Mariposa, CA 95338**

**Date of Grant: 09/03/2014
Application Dated: 08/05/2014**

**Nextivity Incorporated
12230 World Trade Drive
Suite 250
San Diego, CA 92128**

**Attention: Michiel Lotter , Vice President,
Engineering**

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: YETP24512CU
Name of Grantee: Nextivity Incorporated
Equipment Class: **Unlicensed National Information Infrastructure TX**
Notes: **Provider Specific Consumer Signal Booster**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
CC ND	15E	5525.0 - 5580.0	0.048		
CC ND	15E	5715.0 - 5735.0	0.037		

Power listed is conducted at the antenna terminals. This device is part of a booster system operated with FCC ID: YETP24512NU. Operation in 5.15-5.25 GHz band is authorized for indoor use only.

This booster system device shall be operated with frequency selection by network identification and interference avoidance for wireless subsystems as described in this filing for compliance with 20.21(e)(9) and 20.21(e)(7). The antennas used with this signal booster must be installed to provide a separation distance of at least 20 cm from all persons. Users and installers must be provided with the antenna kitting and installation instructions and operating conditions for satisfying RF exposure compliance. This Provider-Specific Fixed Consumer Signal Booster system is approved for operating with the coverage/downlink antenna installed at a fixed location inside a building, and with the installation height of the window-unit/uplink antenna limited to 10 meters above ground for compliance with 47 CFR 27.50. This Consumer Signal Booster is authorized only for operation by and marketing to members of the general public for their personal use in accordance with the requirements of 47 CFR 20.21(a) and 20.21(g).

CC: This device is certified pursuant to two different Part 15 rules sections.

ND: This UNII device complies with the Transmit Power Control (TPC) and Dynamic Frequency Selection (DFS) requirements in Section 15.407(h).

TCB

**GRANT OF EQUIPMENT
AUTHORIZATION**

TCB

Certification

**Issued Under the Authority of the
Federal Communications Commission**

By:

**CKC Certification Services, LLC
5046 Sierra Pines
Mariposa, CA 95338**

**Date of Grant: 09/03/2014
Application Dated: 08/05/2014**

**Nextivity Incorporated
12230 World Trade Drive
Suite 250
San Diego, CA 92128**

**Attention: Michiel Lotter , Vice President,
Engineering**

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: YETP24512CU
Name of Grantee: Nextivity Incorporated
Equipment Class: Part 20 Provider-Specific Consumer Booster (CMRS)
Notes: Provider Specific Consumer Signal Booster

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	27	2110.0 - 2155.0	0.0196	0.309 PM	F9W
	24E	1930.0 - 1990.0	0.0095	0.237 PM	F9W
	22H	869.0 - 894.0	0.0102	0.331 PM	F9W
	27	716.0 - 746.0	0.0115	0.221 PM	F9W

Power listed is radiated; maximum reported EIRP is 0.01963W, 0.0115for part 27 , 0.0095 W for part 24, 0.0102 for part 22. This device is part of a booster system operated with FCC ID: YETP24512NU. Operation in 5.15-5.25 GHz band is authorized for indoor use only.

This booster system device shall be operated with frequency selection by network identification and interference avoidance for wireless subsystems as described in this filing for compliance with 20.21(e)(9) and 20.21(e)(7). The antennas used with this signal booster must be installed to provide a separation distance of at least 20 cm from all persons. Users and installers must be provided with the antenna kitting and installation instructions and operating conditions for satisfying RF exposure compliance. This Provider-Specific Fixed Consumer Signal Booster system is approved for operating with the coverage/downlink antenna installed at a fixed location inside a building, and with the installation height of the window-unit/uplink antenna limited to 10 meters above ground for compliance with 47 CFR 27.50. This Consumer Signal Booster is authorized only for operation by and marketing to members of the general public for their personal use in accordance with the requirements of 47 CFR 20.21(a) and 20.21(g).

TCB

**GRANT OF EQUIPMENT
AUTHORIZATION**

TCB

Certification

**Issued Under the Authority of the
Federal Communications Commission**

By:

**CKC Certification Services, LLC
5046 Sierra Pines
Mariposa, CA 95338**

**Date of Grant: 09/03/2014
Application Dated: 08/05/2014**

**Nextivity Incorporated
12230 World Trade Drive
Suite 250
San Diego, CA 92128**

**Attention: Michiel Lotter , Vice President,
Engineering**

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: YETP24512CU
Name of Grantee: Nextivity Incorporated
Equipment Class: Digital Transmission System
Notes: Provider Specific Consumer Signal Booster

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
CC	15C	5765.0 - 5825.0	0.087		

Power listed is conducted at the antenna terminals. This device is part of a booster system operated with FCC ID: YETP24512NU. Operation in 5.15-5.25 GHz band is authorized for indoor use only.

This booster system device shall be operated with frequency selection by network identification and interference avoidance for wireless subsystems as described in this filing for compliance with 20.21(e)(9) and 20.21(e)(7). The antennas used with this signal booster must be installed to provide a separation distance of at least 20 cm from all persons. Users and installers must be provided with the antenna kitting and installation instructions and operating conditions for satisfying RF exposure compliance. This Provider-Specific Fixed Consumer Signal Booster system is approved for operating with the coverage/downlink antenna installed at a fixed location inside a building, and with the installation height of the window-unit/uplink antenna limited to 10 meters above ground for compliance with 47 CFR 27.50. This Consumer Signal Booster is authorized only for operation by and marketing to members of the general public for their personal use in accordance with the requirements of 47 CFR 20.21(a) and 20.21(g).

CC: This device is certified pursuant to two different Part 15 rules sections.